



# Yes we can... speak

## New generation of price checkers



New POZONE Price Checkers are the customer self-service terminals, which apart from the main function of verifying the products prices allow displaying the information about product, in- store promotions, seasonal sales or upcoming events.

The newest generation devices keeping their usable functionality thanks modern design and new functions are completely suitable to the store arrangement.

Audio price checking is an absolutely new

feature in such a kind of devices. Invaluable help for individuals having the problem with reading the price from the display.

Displaying the advertising graphics and replaying connected with them audio files are specific functions defining price checkers as multimedia points used in time, when the customers does not make the readouts. Possibility of graphics self-preparing allow to display the elements with visual identification of customer.

[www.pozoneintl.com](http://www.pozoneintl.com)



- Reading performance
- External bar code scanner
- Audio files playing
- TFT 4,3 " colour graphic display
- Communication with computer system



SPECIFICATIONS									
Price checker version	RS			LAN			Wi-Fi		
Price checker type	RLT	RWT	RFT	LLT	LWT	LFT	WLT	WWT	WFT
Bar code scanner									
linear imager	✓			✓			✓		
laser omnidirectional		✓			✓			✓	
area imager			✓			✓			✓
Bar codes	EAN13, EAN8, EAN128, UPC-A, UPC-E, Code 39, Code 128, Code 93 and othe standard bar codes								
Dimensions	197 mm (W) x 173 mm (S) x 137 mm (G)								
Weight	1,4 kg								
Display	graphic TFT with the backlight 4,3" (480x272 )								
Power supply	24 – 60 V DC								
Interface	RJ45 (RS232 +remote power supply) DSUB9 (hand held bar code scanner) USB (pendrive memory) Local power supply: 5,5/2,5 standard socket			RJ45 (LAN Standard 100Mb/s + remote power supply) DSUB9 (hand held bar code scanner) USB (pendrive memory) Local power supply: 5,5/2,5 standard socket			SMA socket(antenna) DSUB9 (hand held bar code scanner) USB (pendrive memory) Local power supply:5,5/2,5 standard socket		
Environmental									
Operating temperature	0°C – 40°C								
Humidity	40% - 80% (non- condensing)								
Accessory									
necessary to order separately	Power supply 33V/1,6A (A65)			Power supply 33V/1,6A (A65)			Power supply 33V/1,6A (A65)		
	MZAS power supply module for RS232 network (MZ3)			PoE power supply					
	MZAS power supply 33V/1,6A (A68)			MZAS power supply module for LAN network (MZ1)					
				Power supply module MRPS 2 4xLAN (MZ6)					
				Power supply module MR 4xLAN (MZ5)					
				MZAS power supply 33V/1,6A (A68)					