



**Features**

- Dual interface cable available ,no need PSU
- 20char. x 2 line Vacuum Fluorescent Display
- Eye-catching bright blue-green font
- Innovative hinge design for quick angle adjustment
- Built-in full-speed USB and high speed RS232 up to 115,200

**Specifications**

Display Method	Vacuum fluorescent Display
Number of Characters	40 characters (20 columns x 2 lines)
Display Color	Blue / green
Brightness	700 cd/m2
Character Type	I. 96 alphanumeric characters II. 14 sets of international Characters: USA, France, Germany, UK, Sweden, Denmark I and II, Italy, Spain, Norway, Japan (Katakana), Slavonic, Russian and Portuguese
Font Size	5x7 Dot Matrix 9.03 mm x 5.25 mm

**Electrical**

Command Set	1. EPSON ESC/POS 2. ADM787/788(option) 3. EMAX (AEDEX) 4. UTC/S, UTC/P 5. CD5220 6. DSP-800 (option)			
Interface	<input type="checkbox"/> RS-232:9600/19200/38400/115200 bps <input type="checkbox"/> USB 2.0			
Option	<input type="checkbox"/> Pass-through: (1) RS232C (2) USB Hub <input type="checkbox"/> Bluetooth wireless connection <input type="checkbox"/> Power adapter			
Power Supply	DC 7V~36V	DC 5V Via USB	DC 7V~36V	DC 5V Via USB
Power Consumption	3~5W			
MTBF	30,000 hrs			
Certification	CE/FCC class A			
Rotation Angle	Vertically: 36 degree ; Horizontal: 270 degree			

**Physical Dimension**

Head (W x D x H)	215 x 57 x 92 mm
Support (H x Ø)	Long: 250 x 34 mm; Short: 117 x 34 mm
Base (W x D x H)	200 x 120 x 27 mm

\* Product specifications & Features are subject to change without prior notice

