



PP620

Thermal Receipt Printer



- > Multiple interface connections, auto-cutter, wall mountable.
- > Support for replay function.
- > Queuing up function.
- > Support QR Code and PDF417.
- > Support order prompt and error alarm functions.
- > Support Windows, Linux, Android, IOS, OPOS, and MacOS.



POZONE

Pozone PP620

Thermal Receipt Printer

Model PP620	
Printing method	Direct thermal
Printing speed	230 mm/s
Paper width	80mm
Column capacity	576 dots/line or 512 dots/line
Interface	USB+Lan /
Line spacing	3.75mm (Adjustable by commands)
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Simplified/Traditional Chinese: 3.0×3.0mm (24×24 dots)
Barcode Character	
Extension character sheet	PC437 (Std.Europe) / (Katakana) / PC850 (Multilingual) / PC860 (Portugal) / PC863 (Canadian) / PC865 (Nordic) / (West Europe) / (Greek) / (Hebrew) / (East Europe) / (Iran) / (WPC1252) / PC866 (Cyrillic#2) / PC852 (Latin2) / (PC858) / (IranII) / (Latvian) / (Arabic) / (PT1511251)
1D Barcode	
2D Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
Input buffer	QR CODE / PDF417
NV Flash	128 Kbytes
	256 Kbytes
Power	
Power adaptor Input	AC 100~240V, 50~60Hz, 2.0A
Printer Input	DC 24V/2.5A
Cash drawer	DC 24V/1A
Physical characteristics	
Weight	0.89 Kg
Dimensions	181×137.7×123mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0~45℃), humidity (10~80%)
Storage environment	Temperature (-10~60℃), humidity (10~90%)
Reliability	
Auto cutter	Partial
Cutter life	1.5 million cuts
Printer head life	150Km
Software	
Emulation	ESC/POS
Driver	Windows/JPOS/Linux/OPOS/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS, Android, Windows

Product specifications & features are subject to change without prior notice.

